

Grade 2 Standard Duty Cylindrical Lock

Architectural Submittal Sheet









Specifications

FOR DOORS:	• 1-3/8" to 1-3/4" thick • Preset for 1-3/4" door		
APPLICATION:	Fits standard 160 and 161 door prep No additional thru-bolt		
BACKSET:	Adjustable - 2-3/8" - 2-3/4" (Optional UL Listed fire latch has fixed backsets, 2-3/8" or 2-3/4")		
CHASSIS:	Heavy-gauge cold rolled steel mechanism Dichromated for corrosion resistance		
FRONT:	1" face width, 1/4" radius with square corner filler for 1-1/8" width.		
STRIKE:	Full Lip Strike standard, ASA and T-Strike optional		
LEVERS:	Philadelphia, Boston, Miami, Memphis and Orlando		
ROSE:	• 2-9/16" Diameter Round Rose, 2-15/16" Square Rose		
LATCHBOLT:	• Adjustable - 2-3/8" - 2-3/4" latch standard, Optional UL fire-rated 2-3/4" or 2-3/8" fixed latchbolts are available.		
HAND:	Non-handed, for Memphis, swap levers to rehand.		
TRIM:	Solid diecast PHL, BSN, MIA, MEM and ORL levers Wrought brass roses Concealed screws		
KEYS:	• Two (2) per Lock		
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers		
INTERCHANGEABLE CORE:	• 6 or 7-pin • Compatible with Best, Falcon & Arrow. Not available with Memphis lever.		
CYLINDER:	• 6-pin Brass Insert Cylinder keyed to 5-pins • Standard High Security and UL437 Cylinders Available		
KEYING:	Options: MK, CMK or GMK / Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) Can be keyed into existing master key systems		
FINISHES:	• 605 (Bright Brass), 606 (US4) Satin Brass, 613 (Oil Rubbed Bronze), 619 (Satin Nickel), 622 (Flat Black), 625 (Bright Chromi- um), 626 (Satin Chrome)		
COMPLIANCES:	Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings		
CERTIFICATIONS, LISTINGS:	 Entry function and optional fixed backset latch only. Certified to ANSI/BHMA 156.2, Grade 2 (fixed backset latch only). UL listed for single doors up to 4'0" x 8'0" when ordered with UL latchbolt, contact factory for details. TAA compliant. Country of origin: KR 		
WARRANTY:	Three (3) year Limited Warranty		

Levers











Philadelphia

Boston

Miami

Memphis

Orlando



www.pdqlocks.com

SF Series

PDQ Functions

FUNCTION	FUNCTION NUMBER	OUTSIDE INSIDE	DESCRIPTION	ANSI NUMBER		
	NON KEYED					
Passage	SF126		Latchbolt operated by lever from either side at all times	F75		
Privacy Bedroom Bathroom	SF176		 Latchbolt operated by lever from either side or emergency release in outside lever Outside lever locked by push button on inside Outside lever unlocked by emergency release from outside, rotating inside lever, or closing door 	F76		
			KEYED			
Storeroom	SF115		 Latchbolt operated from outside by key, inside by lever Outside lever always fixed Inside lever always free Deadlocking (guarded) latchbolt 	F86		
Entrance	SF116	Fixed backset, fire rated, BHMA latch included.	 Latchbolt operated by lever from either side or key in outside lever Outside lever locked by push/turn button on inside When outside lever is locked by push button on inside – key from outside, or rotating inside lever unlocks outside lever When outside lever is locked by pushing and turning the button on the inside, key from outside or rotating inside lever retracts latch but does not unlock outside lever Deadlocking (guarded) latchbolt 	F109		
DUMMY						
Single Dummy	SF211		Pull lever one side No mechanical operation	_		

INDICATES RIGID LEVER

Trim



Round Rose



Square Rose

Finishes





619 (US15) Satin Nickel 622 (US19) Flat Black

625 (US26) Bright Chromium Satin Chromium

626 (US26D)



SF Series

Latches

Non-Keyed Functions

Non-Fire Rated Adjustable Latch (Standard on Non-Keyed Functions)

CODE	DESCRIPTION
ADJ	Adjustable non-fire rated latch, 1" face width with 1/4" radius corner with 1-1/8" square corner filler

Optional UL Fire Rated/BHMA Certified Fixed Backset Latch

CODE	DESCRIPTION
234	Fixed 2-3/4" backset fire rated latch, Square Corner 1-1/8" face
238	Fixed 2-3/8" backset fire rated latch, Square Corner 1" face
238R	Fixed 2-3/8" backset fire rated latch, Radius Corner 1" face

Keyed Functions

UL Fire Rated/BHMA Certified Fixed Backset Latch (Standard on Keyed Functions)

CODE	DESCRIPTION
234	Fixed 2-3/4" backset fire rated latch, Square Corner 1-1/8" face
238	Fixed 2-3/8" backset fire rated latch, Square Corner 1" face
238R	Fixed 2-3/8" backset fire rated latch, Radius Corner 1" face

