

Extra Heavy Duty Bored Deadbolt

Architectural Submittal Sheet

Typical Applications

- Commercial
- Government
- Hospitality
- Institutional
- Military
- Multi-family
- Offices
- Retail





Specifications

FOR DOORS:	1-3/4" thick standard, contact factory for other thicknesses			
DOOR PREP:	• 2-1/8" DIA			
BACKSET:	• 2-3/4" (Default) • 2-3/8" available			
FRONT:	• 2-1/4" x 1-1/8" or 2-1/4" x 1" • Stainless Steel or Wrought Brass			
STRIKE:	• 2-3/4" x 1-1/8" • Stainless Steel or Wrought Brass • Dust Box Included			
DEADBOLT:	• 1" Throw • Brass Bolt containing two concealed 1/4" case-hardened Steel Roll Pins			
HAND:	• Non-handed			
TRIM:	Wrought Brass Scalp Reinforced Zinc Diecast Rose			
KEYS:	• Two (2) per Lock			
KEYWAYS:	• SCC standard (Schlage C Compatible) • Also available in keyways of other manufacturers			
CYLINDER:	6-pin Brass Mortise Cylinder keyed to 5-pins, SFIC			
KEYING:	 Options: MK, CMK or GMK Zero Bitted (KO), Keyed Different (KD) or Keyed Alike (KA) Can be keyed into existing master key systems 			
FINISHES:	• 605 (US3) - Bright Brass, 606 (US4) - Satin Brass, 613 (US10B) - Oil Rubbed Bronze, 625 (US26) - Bright Chrome or 626 (US26D) - Satin Chrome			
WARRANTY:	One (1) year Limited Warranty			
LISTINGS:	 UL 10C listed, 3-hour fire rated as auxiliary locks for A label single doors UL 10B listed for neutral pressure doors 			



KT Series

PDQ Functions

FUNCTION	FUNCTION NUMBER	OUTSIDE INSIDE	DESCRIPTION	ANSI NUMBER
Entrance	116		• Lock or unlock by key from outside, by thumb turn from inside	E1151
Single Cylinder	121		 Lock or unlock by key from outside Blank mortise cylinder on inside 	E1161
Single Sided	125		Deadbolt by inside thumb turn only Blank mortise cylinder on outside	E11111
Double Cylinder	137		Lock or unlock by key from both sides	E1141
Classroom	148		 Lock or unlock by key from outside Turnpiece inside retracts deadbolt, but will not project it 	E1171

Finishes



